### L350 - The Authentic T-Shirt Company<sup>®</sup> Ladies' Pro Team Tee

#### GARMENT MEASUREMENTS

Finished Medsurements in increas											
Size	XS	S	М	L	XL	2XL	3XL	4XL			
Chest	18	19	20	21 1/2	23	24 1/2	26 1/2	28 1/2			
CB Length	25	$25 \ 1/2$	26	27	28	29	29 1/2	30			

\* Chest is measured 1" down from the armhole (1/2 measurement). CB length is measured from the center of the back neck seam to the hem.

#### WOMEN'S SIZING CHART

	XS	S	М	L	XL	2XL	3XL	4XL
Numeric Size	2	4-6	8-10	12-14	16-18	20-22	24-26	28-30
Bust	32-34	35-36	37-38	39-41	42-44	45-47	48-51	52-55

Bust: Measure under your arms at the fullest part of your chest.



#### PRINTING INSTRUCTIONS FOR POLYESTER WICKING FABRICS

Due to the nature of 100% polyester performance fabrics, special care must be taken throughout the printing process. Here are some tips to effectively decorate our performance products.

• Garment temperature must not exceed 320°F or 160°C. Exceeding this temperature will cause the fabric to shrink, become wavy or cause dye migration.

• Dryer temperature and belt speeds must be changed accordingly for polyester fabric.

• If flashing these garments, do not exceed 1-2 seconds. Anything longer may damage the fabric as stated above.

• Screen Printing: These garments require the use of poly inks that cures at a lower temperature. A Dyno Grey base blocker on all colours and a second white base blocker on all dark colours are recommended. Please consult your ink supplier for more information.

• Polyester requires a longer cooling time than cotton. Avoid overlap of garments and screen-print/heat transfer until the garments are cooled. Failure to cool the fabric prior to stacking into a printer's fold may cause the fabric and applied ink to stick together.

• Heat Transfers: Poly mark heat transfers need to be created with an anti-migration layer in the design. This process can only be done on white or very light colour shirts. Inks used in printing paper design needs to be darker than the base fabric or colour will migrate with the fabric colour resulting in a bleeding effect.

• Sublimation Printing: As noted for the poly mark heat transfers, this process can only be done on white or very light colour shirts. Inks used in printing paper design needs to be darker than the base fabric or colour will migrate with the fabric colour resulting in a bleeding effect.

• If you heat press these garments, you must adjust the time, temperature and pressure. Failure to do so may damage the fabric as stated above.

• A test sample run is recommended, especially if you have a large order or if your printer does not specialize in printing on performance fabrics.





# Available Colours and PMS Colours

Textile fabric colours are subject to dye lot variation and will not be exact match to print pantone reference





# **THE AUTHENTIC T-SHIRT COMPANY®** Pro Team Ladies' Tee - L350

# **Product Features:**

- 6-oz, 100% polyester jersey knit
- Easy care fabric
- Moisture wicking
- Tagless label
- Slightly contoured side seams for feminine fit

### Ladies' sizes XS-4XL

Corresponding styles;

Pro Team Tee - S350 Pro Team Youth Tee - Y350 Pro Team Long Sleeve Tee - S350LS Pro Team Long Sleeve Youth Tee - Y350LS Pro Team Youth Short - Y355 Pro Team Short - S355

### Fabric Detail:







# Smart Uses:

Keep your cool and level any playing field with a pro team tee!

- Schools/camps
- Gift giving
- Sports teams & events
- Coaches/athletes
- Donations/door prizes
- And much more!

January 2013

Due to the nature of 100% polyester performance fabrics, special care must be taken throughout the screen printing process.